



Xplore CFL 35 micro cast film line

A high quality add-on for the Xplore MC 15 HT or MC 40



Fast screening of new film formulations:

a 35 mm wide lab cast film line

This micro cast film line is based on Xplore's proprietary technology. In combination with our micro compounder, it is now possible to obtain cast film with just 5 g of material in 10 minutes. In this way, material need and development time is drastically reduced, and considerably less R&D budget is needed.

A representative test film is now obtained in a few minutes with only a fraction of material used compared to conventional film development on laboratory equipment.

This film line is especially useful when only a small amount of material is available, or when expensive additives are used, like nano-tubes, active pharmaceutical ingredients, etc..

With our continuous feed kit, which consists of a mountable barrel hopper and forced feeding screws, it is now also possible to process larger samples into extremely long film via continuous extrusion.

Film characteristics

The micro cast film line can produce cast film and sheet with 5 - 10 g samples. The integrated air knife enables to process film up to a width of ca. 35 mm.

The cast film drawing speed is between 100 and 5000 mm/min, and the cast roll of the first calender can be adjusted with increments of 1 mm/min.

The winding roll of the second calender is torque controlled (its diameter will grow during the test run), and the winding torque can be adjusted with increments of 1 Nmm.


In combination with our micro-compounder, which is equipped with throughput control, Xplore enables you to produce a uniform film thickness without the use of a gear pump. Latest results show that films as thin as 5 μm can be obtained without any holes.



Benefits:

- Large operating window
- Small footprint
- Very slow cast speeds possible
- Easy to operate, hence fast results
- Necking is prevented by an air knife
- Can be retrofitted into an existing lab-scale extrusion line





Technical Specifications:

- Die with 12 filaments (\varnothing 0,75 mm) or an optional custom amount of filaments
- Die is heated by a heating band and measured by a thermocouple
- Port for pressure measurement
- Maximum heating temperature: 450 °C
- Exchangeable filter package
- Heating time (from 20 to 240 °C): 10 min
- Supply voltage: 208 - 240 V AC, 50/60 Hz
- Overall dimensions (h x b x d): 10 x 25 x 10 cm
- Approximate MFD weight: 2 kg
- Optional pressure transducer
- Optional 2 zone quench box incl. wetting unit (avivage)
- Optimal melt strength measurement
- Optional feeding unit and feeding control unit
- Optional dedicated table set up for vertical spinning in combination with an, e.g. Xplore compounder and Xplore winder unit

Xplore Instruments BV

Arendstraat 5
6135 KT, Sittard
The Netherlands

Tel: +31 46 208 97 70
Fax: +31 46 208 97 71

info@xplore-together.com
www.xplore-together.com
Trade Register: 60040114